

ARM602-3

3/8" Digital Torque Adapter

- Static torque measurement
- Standard functions: torque setting, measurement setting, mode setting
- Operation in both clockwise and counter-clockwise directions
- LCD display shows N·m (or kg·cm, in-lb, ft-lb) measurements
- Audible torque confirmation by means of buzzer
- Easy to set up Set, Peak or Track modes

Torque Range
4-80 Nm



Model Number	ARM602-4	ARM602-3	Model Number	ARM602-4	ARM602-3
Drive	1/2" Square	3/8" Square	Resolution	1 kg·cm, 0.1 N·m, 1 in-lb, 0.1 ft-lb	
Length	75 mm (3")		Auto Shut-Off	After 1 Minute of No Use	
Width	47 mm (1-27/32")		Operating Temperature	0-50°C	
Height	48 mm (1-29/32")		Storage Temperature	-10-60°C	
Accuracy	+/- CW +/- 2% +/-(CW) +/- 3%		Battery	Qn In Cell CR2032 X 2 (Included)	
Measured Torque Range	5-200 Nm (4-150 ft-lbs)	4-80 Nm (0-60 ft-lbs)	Tool Weight	0.20 kg (0.44 lbs)	0.14 kg (0.31 lbs)

The certification of accuracy provided per ASME and ISO Standards is 20% to 100% of full scale.