

Shut-off Impulse wrench

YLT-Series

HIGH PERFORMANCE



NEW!

YLT Series

- **Maximum accuracy**
Extreme accurate and fast. Repeatability, new principle: shut-off valve and reset
- **Maximum durability**
Check valve mechanism reduces load on the O-ring inside the oil pulse mechanism.
- **Maximum ergonomics**
Ergo touch / Ergo grip / Ergo trigger
- **Maximum environment**
Reduction of CO2 emission / Low noise / Low vibration

Yokota Impulse Wrenches

- Have proven themselves worldwide in the leading car- and general assembly industry, tightening threaded fasteners.
- Are light, powerful and small and very importantly they have no kick-back.
- Are extremely low weight and good for use with non-lubricated air.

Type	Square/hex drive	Bolt capacity mm	RPM	Torque Nm*	Air-cons l/s	Inlet-thread	Weight kg	Hose diameter mm	Length A mm	Spindle offset B mm	Vibration m/s ²	Noise level dB(A)
YLT50A	1/4" 6K	5	4.300	4,5 - 8	4,2	PT 1/4"	0,95	6,5	164	22,5	1,1	70
YLT60A	1/4" 6K	6	5.300	60 - 13	5,5	PT 1/4"	0,95	6	164	22,5	1,4	72
YLT70A	1/4" 6K	6-8	6.800	13 - 28	6,0	PT 1/4"	1,01	6	177	23	1,8	74
YLT50E	3/8" 4K	5	4.300	4,5 - 8	4,2	PT 1/4"	0,95	6,5	164	22,5	1,1	72
YLT60E	3/8" 4K	6	5.300	7 - 15,5	5,5	PT 1/4"	0,95	6	164	22,5	1,4	72
YLT70E	3/8" 4K	6-8	6.800	15 - 32	6,0	PT 1/4"	1,01	6	177	23	1,8	74
YLT80E	3/8" 4K	8	6.800	30 - 55	7,3	PT 1/4"	1,12	6	187	24,5	1,9	78
YLT110E	1/2" 4K	10-12	5.800	50 - 85	8,3	PT 1/4"	1,51	9,5	194	28,5	1,8	81
YLT120E	1/2" 4K	12	5.400	70 - 115	8,6	PT 1/4"	1,79	9,5	201	31	2,2	83
YLT140E	1/2" 4K	14	5.200	110 - 150	11,8	PT 1/4"	2,08	9,5	214	32,5	5,2	85
YLT150	3/4" 4K	16	4.400	140 - 210	11,8	PT 1/4"	2,95	10	237	38,5	6,2	85

* The specified torques are to be used as a guidance only.