

## Specifications

Diameter (mm)	Thickness (mm)	Bore (mm)	Grain	Grit	Hardness	Packing Outer Box (pcs×inner box)	Maximum operation speed
100	4	16	A/WA	24	N · P	200pcs (25pcs×8boxes)	72m/s (4,300m/min)
				36	P		
	6		A/WA · WA	24 · 36	N · P		
125	6	22	A/WA	24 · 36	N · P	100pcs (25pcs×4boxes)	72m/s (4,300m/min)
			WA	24 · 36	N · P		
			C	24	P		
150	6	22	A/WA	24	N · P · S	100pcs (25pcs×4boxes)	72m/s (4,300m/min)
				36	N · P		
			WA	24 · 36	N · P		
			C	24	N		
180	3	22	A/WA · WA	36	P	50pcs (25pcs×2boxes)	72m/s (4,300m/min)
			A/WA	24 · 36	P		
	4		WA	36	P		
			A/WA	24	M · N · P · S		
	36			N · P			
	6		WA	24	K · M · N · P		
				36	K · N · P		
			C	24	N · P		
36		P					
205	6	22	A/WA	24	N · P	50pcs (10pcs×5boxes)	72m/s (4,300m/min)
				36	N · P		
			WA	24	N · P		
				36	N · P · Q		
			C	24	N		
230	6	22	A/WA · WA	24	N	50pcs (10pcs×5boxes)	72m/s (4,300m/min)

For stones

Diameter (mm)	Thickness (mm)	Bore (mm)	Grain	Grit	Hardness	Packing Outer Box (pcs×inner box)	Maximum operation speed
100	6	16	GC	24 · 36 · 46 · 60 80 · 120	P	200pcs (25pcs×8boxes)	72m/s (4,300m/min)
125	6	22	GC	24 · 36	P	100pcs (25pcs×4boxes)	72m/s (4,300m/min)
180	6	22	GC	24	P	50pcs (25pcs×2boxes)	72m/s (4,300m/min)

◆ The unit of diameter, thickness and bore is the mm.

◆ Each product lines are available in different sizes, please contact us.

Product Code

## Article



Working surface

\*GC46,60,80,120 are green color wheels.

## Package

