

Specifications

| Diameter (mm) | Thickness (mm) | Bore (mm) | Grain | Grit | Hardness | Packing Outer Box (pcs×inner box) | Maximum operation speed | |
|---------------|----------------|-----------|------------|--|----------|-----------------------------------|-------------------------|---|
| 100 | 2 | 16 | AC | 36 · 46 · 60 · 80 · 100 120 · 150 180 | - | 200pcs (20pcs×10boxes) | 72m/s (4,300m/min) | |
| | | | WA | 36 · 46 · 60 · 80 100 · 120 | | | | |
| | | | GC | 60 · 80 · 100 · 120 · 150 | | | | |
| | 3 | 16 | AC | 46 · 60 | | | | |
| | | | WA | 36 · 46 · 60 · 80 | | | | |
| 125 | 2 | 22 | AC · WA | 46 · 60 · 80 · 100 · 120 | - | 50pcs (25pcs×2boxes) | 72m/s (4,300m/min) | |
| | 3 | | AC · WA | 36 · 46 · 60 · 80 · 100 · 120 | | | | |
| 150 | 2 | 22 | AC | 46 · 60 · 80 · 100 · 120 | - | 50pcs (25pcs×2boxes) | 72m/s (4,300m/min) | |
| | | | WA | 46 · 60 · 80 · 120 | | | | |
| | 3 | | AC | 36 · 46 · 60 · 80 | | | | |
| | | | WA | 80 | | | | |
| 180 | 2 | 22 | AC · WA | 46 · 60 · 80 · 100 120 · 150 · 180 | - | 50pcs (25pcs×2boxes) | 72m/s (4,300m/min) | |
| | | | C | 80 | | | | |
| | 3 | | AC | 24 · 36 · 46 · 60 80 · 100 · 120 | | | | |
| | | | WA | 36 · 46 · 60 80 · 100 · 120 | | | | |
| | | | C | 24 | | | | G |
| | | | GC | 60 | | | | - |

◆ The unit of diameter, thickness and bore is the mm.

◆ Each product lines are available in different sizes, please contact us.

Product Code

Article



Working surface

Package and backup Pad



Backup Pad
Each inner box includes a backup pad.

Precautions

▶ Always use backup pad.