




YX-SERIES : Pistol grip models with square shank



Exterior		Model	Bolt Capacity	Free Speed (Approx.) rpm	Load Air Consumption (Approx.) l/min(ft ³ /min)	Torque Adjustable Range (reference) N·m		Overall Length (about) mm(in)	Weight Less Socket kg(lb)	Spindle Offset (about) mm(in)	Square Drive mm(in)	Noise Level Load 1m dB(A)	Air Inlet Thread (Pipe Thread) Rc	Air Hose Size mm(in)
Body	Spindle					Air Pressure(dynamic) 0.6MPa (85 lb/in ²)								
Pistol	Sq.	YX-180•180E	M4~M6	11000	250 (8.8)	18~29	169 (6.7)	1.00 (2.2)	23.0 (0.9)	9.5 (3/8)	83	1/4	9.5 (3/8)	
		YX-280•280E	M6~M8	10500	300 (10.6)	25~39	180 (7.1)	1.07 (2.4)	23.0 (0.9)	9.5 (3/8)	83	1/4	9.5 (3/8)	
		YX-380•380E	M8	9000	300 (10.6)	34~49	180 (7.1)	1.24 (2.7)	25.5 (1.0)	9.5 (3/8)	81	1/4	9.5 (3/8)	
		YX-500•500E	M8~M10	8200	350 (12.4)	31~51	173 (6.8)	1.44 (3.2)	26.5 (1.0)	9.5 (3/8)	77	1/4	9.5 (3/8)	
		YX-700•700E	M8~M10	8000	400 (14.1)	44~80	185 (7.3)	1.64 (3.6)	26.5 (1.0)	9.5 (3/8)	79	1/4	9.5 (3/8)	
		YX-900•900E	M10	7000	400 (14.1)	75~120	201 (7.9)	2.00 (4.4)	30.5 (1.2)	12.7 (1/2)	80	1/4	9.5 (3/8)	
		YX-1100•1100E	M10~M12	4700	450 (15.9)	85~135	210 (8.3)	2.10 (4.6)	30.5 (1.2)	12.7 (1/2)	82	1/4	9.5 (3/8)	
		YX-1400•1400E	M12~M14	6000	500 (17.7)	100~170	216 (8.5)	2.73 (6.0)	33.5 (1.3)	12.7 (1/2)	83	1/4	9.5 (3/8)	
		YX-1900•1900E	M12~M14	5800	500 (17.7)	130~220	224 (8.8)	3.40 (7.5)	35.5 (1.4)	12.7 (1/2)	81	1/4	9.5 (3/8)	
		YX-2400•2400E	M14~M16	4200	550 (19.4)	150~240	236 (9.3)	4.10 (9.0)	37.0 (1.5)	12.7 (1/2)	81	1/4	9.5 (3/8)	
		YX-3000	M16~M18	4500	600 (21.2)	230~350	246 (9.7)	4.60 (10.1)	40.0 (1.6)	19.0 (3/4)	80	1/4	12.7 (1/2)	
YX-4500	M18~M20	3400	700 (24.7)	305~390	293 (11.5)	9.8 (21.6)	49 (1.9)	19.0 (3/4)	87	3/8	12.7 (1/2)			

■ All models have a hose nipple and 1 or 2pcs hexagon wrenches.
Torque specification is a guideline only. Please select the suitable tool to meet the work condition.